

1		2		3		4																																																																	
A	Datos técnicos/ Technical data: <table border="1"> <tr> <td>According to/ En referencia a:</td> <td>1327015</td> </tr> <tr> <td>Operating temperature range/ Rango de temperatura:</td> <td>-40°C a/to 80°C</td> </tr> <tr> <td>Weight/ Peso:</td> <td>26,5 gr</td> </tr> </table> <table border="1"> <tr> <td>PIN 1</td> <td>+24V</td> </tr> <tr> <td>PIN 2</td> <td>GND/MASA</td> </tr> </table>							According to/ En referencia a:	1327015	Operating temperature range/ Rango de temperatura:	-40°C a/to 80°C	Weight/ Peso:	26,5 gr	PIN 1	+24V	PIN 2	GND/MASA	A																																																					
	According to/ En referencia a:	1327015																																																																					
Operating temperature range/ Rango de temperatura:	-40°C a/to 80°C																																																																						
Weight/ Peso:	26,5 gr																																																																						
PIN 1	+24V																																																																						
PIN 2	GND/MASA																																																																						
B								B																																																															
C								C																																																															
D	VIEW/VISTA B VIEW/VISTA A							D																																																															
E								E																																																															
F	<table border="1"> <tr> <td rowspan="5">Modification</td> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td>Drawn</td> <td rowspan="5"> </td> </tr> <tr> <td>3</td> <td></td> <td></td> <td></td> <td></td> <td>04/08/20 S.F.</td> </tr> <tr> <td>2</td> <td></td> <td></td> <td></td> <td></td> <td>Checked</td> </tr> <tr> <td>1</td> <td></td> <td></td> <td></td> <td></td> <td>04/08/20 E.L.</td> </tr> <tr> <td>nº</td> <td>Modified</td> <td>Date</td> <td>Reason</td> <td>General Tolerance</td> <td>Assembly</td> </tr> <tr> <td colspan="5">Comments</td> <td>ISO 2768 c-K</td> <td>Part name</td> <td>Switch/Interrupor</td> </tr> <tr> <td colspan="5"></td> <td>Material</td> <td>ID. Reference</td> <td>2260645</td> </tr> <tr> <td colspan="5"></td> <td>-</td> <td>Scale: 1/1</td> <td rowspan="2"> </td> </tr> <tr> <td colspan="5"></td> <td>-</td> <td>Review: 0</td> </tr> </table>							Modification	4					Drawn		3					04/08/20 S.F.	2					Checked	1					04/08/20 E.L.	nº	Modified	Date	Reason	General Tolerance	Assembly	Comments					ISO 2768 c-K	Part name	Switch/Interrupor						Material	ID. Reference	2260645						-	Scale: 1/1							-	Review: 0	F
Modification	4					Drawn																																																																	
	3					04/08/20 S.F.																																																																	
	2					Checked																																																																	
	1					04/08/20 E.L.																																																																	
	nº	Modified	Date	Reason	General Tolerance	Assembly																																																																	
Comments					ISO 2768 c-K	Part name	Switch/Interrupor																																																																
					Material	ID. Reference	2260645																																																																
					-	Scale: 1/1																																																																	
					-	Review: 0																																																																	
PG/18/02 rev.1 1		2		3		4																																																																	